

Brikerbox Enterprise**AR7500****Overview**

The Brikerbox Solution integrates phone calls via digital line module, becoming a feature-rich Private Branch Exchange (PBX) system that supports seamless communications between conventional phone lines, IP Phone, and other telecommunication devices, all features and functionalities that otherwise not available in conventional PBX. The interconnectivity enabled by Brikerbox provides users with the ability to call PSTN, GSM, CDMA or other IP extensions, through IP Phone, softphone or analog phone connected via Analog Telephone Adapter (ATA).

Brikerbox AR7500 Series is the next generation voice communication platform for the medium to large enterprises. Designed as an open, scalable and highly reliable telephony solution, the Brikerbox AR7500 Series is able to accept 3000 online accounts and effectively handle calls up to total 600 concurrent calls. With the Brikerbox AR7500 Series, standard SIP phones can be easily integrated in your office. You may integrate with all IP phone, Video phone and the analog telephone adapter with protocol SIP and H323 to build up the VoIP network deployment in minutes.

Benefits**1. Save money on cables**

With Brikerbox, telephones system can be operated over Ethernet cable, existing data cables can be used. Does not require a separate cabling.

2. Save money on capabilities

Simple device with great capabilities. Brikerbox got many things in one box. Integrated audio and video conference system, multi-layer Interactive Voice Response, call center, call recording, voicemail system, digital and analog phone technologies, and more.

3. Save money on telco bill

Brikerbox LCR will automatically route calls to a cheaper line. Brikerbox with LCR will save up to 60%. It also save money by security, caller authentication with PIN and call limit with prepaid and postpaid billing system.

4. Save money on maintenance

Easy maintenance and configuration for daily bases usage. Support Department can remotely maintain the systemsales package.

5. Save money for the future

Now and Next Generation Network (NGN) ready. IP communication, Skype, Fax over IP, digitized fax documents, a bridge for multi-protocol, supports multi-vendor CPE.



IP PBX Brierbox AR7500 Specification

Hardware

- Form factor rackmount 2U
- Dimension 426 x 650 x 89 mm
- Internal recording storage up to 25.000 hours
- Network interface dual Gigabit Ethernet (GbE)
- Support digital line E1 / T1 up to 4 ports
- Support analog line FXO / FXS up to 24 ports
- Support mixed digital line and analog line
- Built-in 4 channels software FAX server
- 3000 online phones
- 600 concurrent calls
- Redundant dual storage RAID1
- Serial Attached SCSI (SAS)
- Redundant Power Supply 740 watt

IP PBX system

Features

- Support SIP and H323 simultaneously
- Support SIP TCP, UDP and TLS
- Support Secure RTP (SRTP)
- Support voice codec transcoding
- Support voice and video codec passthrough
- Multiple voice codec G711u, G711a, GSM, iLBC
- Multiple video codec H264 and H263
- In-band / RFC2833 / SIP-INFO DTMF translation
- Multiple trunks
- Unlimited DID trunks to extensions
- Support gateway trunk mode per trunk
- Support options keepalive
- NAT session keepalive
- Caller ID detection
- Trunk hunting and failover
- Support call hold and call waiting
- Support phone multi conference
- Voice calling and audio conference room
- Video calling and video 3 - way conference
- Support blind and attended transfer
- In-call call transfer
- Call forward unconditional, unavailable, busy
- Per calling number forward and rejection
- Blacklist of number patterns
- Call park and retrieve
- Remote extension registration via internet
- Direct line to extension (DID to extension)
- Direct line by called number (DID by number)
- Echo cancellation
- Flexible numbering plans
- Flexible dialing plans
- Application Programmable Interface (API)
- Disaster recovery
- High availability
- Call privilege grouping
- Configurable music on hold
- Multiple channels FAX server
- Support T.38 FAX
- Support T.30 FAX passthrough
- Fax forwarding to email
- Complete voicemail system
- Complete calendar system
- Hot forward
- Hot Desking
- Call center ready

- Multi Tenant Unit
- Call timer by extension
- Seamless integration with legacy PBX
- ACD (Automatic Call Distribution)
- LCR (Least Cost Routing)
- LCD (Least Cost Dialing)
- Billing system and CDR reports
- Voice recording and call monitor

Interactive voice response

- Multilayer IVR
- Work time / holiday setting for different IVR
- Configurable greeting prompts
- Music on ringing extensions
- Forward to voice mail on no-answer
- Hot key to operator

Billing administration

Management and reporting

- Customers balance management
- Voucher management
- Multi-currencies support
- Reporting statistics
- Monthly and daily reporting
- Earnings calculation and markup / margin on report
- Monthly traffic reports (pie chart)
- Daily load
- Compare call-load with previous days
- Export report to PDF and CSV

Rate engine

- Least cost routing
- Least cost dialing management
- Prepaid and postpaid system
- Flat billing system
- Progressive billing system
- Expiry of rates
- Import rate cards
- Rate-card simulator
- Trunk / provider management
- Failover trunks
- Batch update for rates
- Calling packages management

Server administration

System management

- Web based configuration with session control
- User and administrator configuration mode
- Reboot and shutdown from web based
- CLI (Command Line Interface) for configuration
- System event syslog

Network management

- DHCP service server
- DHCP client
- Static IP configuration
- Virtual Ethernet
- Virtual Private Network (VPN)
- VLAN configuration
- Static routing configuration
- NTP service server
- NTP client